



IN THE UNITED STATES PATENT  
AND TRADEMARK OFFICE

DOCKET PA1.615

In re Patent Application of

GROUP NUMBER 3732

JOHNSON, GARY E.

Serial No.: 09/204,866

Filed: 3 Dec. 1998

I hereby certify that this correspondence  
is being deposited with the United  
States Postal Service as express  
mail in an envelope

ADDRESSED TO:


Commissioner of Patents  
United States Patent and  
Trademark Office  
Mail Stop AF

P.O. Box 1450

Alexandria, VA 22313-1450

For: POWERED CUTTING  
SURFACE WITH PROTECTIVE  
GUARD FOR EQUINE TEETH  
Group: 3732

On 10 October 2003

  
John E. Halamka

Examiner: Mr. John J. Wilson  
Primary Examiner

Dated: 10 October 2003  
Palos Verdes Estates, California

RENEWED PETITION UNDER 37 CFR 1.137(b)  
AND REQUEST FOR RECONSIDERATION UNDER 37 CFR 1.137(b)  
IN RESPONSE TO DECISION DISMISSING PETITION TO REVIVE  
AFTER ABANDONMENT  
FROM FINAL ACTION DATED 6/12/2002

Honorable Commissioner of Patents and Trademarks

P.O. Box 1450

10/16/2003 AWOHDAF1 00000065 193935 09204866

Alexandria, VA 22313-1450

02 FC:2801

385.00 DA

Office of Petitions: Attn: Mr. Paul Shanoski

03 FC:2202

135.00 DA

04 FC:2809

385.00 DA

Dear Mr. Shanoski:

Responsive to the Decision Dismissing Petition, Mailed August 12,  
2003, Applicant and his attorney wish to thank you for the Notice of  
steps to be taken after final to maintain pendency of the above identified  
application with Allowable claims 2,3,7,8,12,13 and 16-29.

Applicant's Attorney requests the examination of this response in  
an expedited manner which applicant's attorney believes the fee to be  
\$135.00. Authorization to charge to Deposit account 08-0207 this fee  
and any other fee due on the submission of this Response is attached

RECEIVED

OCT 16 2003

hereto. Applicant's Attorney understands that other fees which might be applicable to this submission such as filing a submission after final rejection in the sum of \$385 for a small entity as well as a request for continued examination in the sum of \$385 and fully authorizes any fees whatsoever of this application to be charged to Deposit account 08-0207.

Applicant's Attorney has also attached a Terminal Disclaimer to Accompany Petition and authorizes the payment of the Terminal Disclaimer fee from Deposit Account 080207. Applicant's attorney further authorizes the payment of any fee for the filing of this Renewed Petition under 37 CFR 1.137(b) from Attorney's deposit Account 080207.

When applicant's attorney contacted the United States Patent Office regarding this matter, he was concerned that he was not listed as attorney of record for the above-identified application. He faxed a copy of the Power of Attorney to the United States Patent Office and herein attaches another copy and prays that the file for this application be updated to reflect John E. Halamka as the Attorney of Record in this matter. The full identification should be:

John E. Halamka  
P.O. Box 207  
Palos Verdes Estates, CA 90274  
310-316-6100  
Fax 310-541-8290  
Email - [halamka@usc.edu](mailto:halamka@usc.edu)

A formal Change of Correspondence Address Application is attached hereto.

Enclosed are 10 pages of formal substitute pages to the claims reflecting the cancellation of claims 1, 4-6, 9-11, 14 and 15 by inserting (canceled) after each number as well as preserving the remaining allowed claims. Applicant's attorney did not understand that the claims not allowed must be formally cancelled. Therefore the cancellation of the claims at this time does not add new matter to the application but simply places the allowed claims in condition for allowance thereby preserving the allowed matter for the applicant. The action by Applicant's Attorney of not canceling the identified claims was unintentional and inadvertently omitted from the Response to the Office Action Made Final dated June 12, 2002. The first response to Final was filed 11 September 2002 and upon notification that the claims were still not in condition for allowance, applicant's attorney submitted a second response on 22 December 2002 which was 10 days beyond the maximum time to respond which created the current problem but still failed to place the

application in condition for allowance as the claims were not allowed still not cancelled.

Applicant's attorney respectfully submits that this action of canceling the non-allowed claims will bring the application into condition for allowance and preserve the valuable rights of the applicant. No new matter has been added to the application. It is requested that the following substitute pages of claims be allowed to be entered into the file and the application be passed on for issue.

IN THE CLAIMS:

Applicant by his Attorney of Record, John E. Halamka, hereby requests the cancellation of claims 1, 4-6, 9-11, 14 and 15.


Kindly find substitute pages 23 through 32 attached that reflect the cancellation of claims. Applicant's attorney respectfully requests the substitute pages be added to the application in place of the original filed pages.

As this response is filed within the two months from the mailing of the Decision Dismissing Petition, applicant's attorney believes that no additional fees are due. However, applicant's attorney authorizes any fees found to be due to be charged to Deposit Account 08-0207.

In case the examiner finds the application is not yet in condition for allowance, applicant's attorney respectfully requests immediate notification of any deficiency to which applicant's attorney will immediately respond to correct such deficiency, if any.

Timely notice of allowance of this application is hereby respectfully requested.

Respectfully submitted,

  
John E. Halamka  
Attorney of record



20  
F

1 WHAT IS CLAIMED IS:

2 1. (Cancelled) An arrangement of a tool insertable into the mouth of a  
3 house for the care and maintenance of teeth while providing  
4 protection of soft tissue within the mouth of the horse and comprising  
5 in combination:  
6 an electric rotary motor having a means to hold said tool along the axis  
7 of rotation of said motor, said tool having a tooth cutting surface of a  
8 preselected size and shape;  
9 a shaft having one end mounted to said cutting surface and the other  
10 end attachable to said motor holding means thereby supplying  
11 rotational motion to said tool;  
12 a shaft support means through which said shaft may be removably  
13 inserted;  
14 a hand piece having a channel through which said shaft support means  
15 is removably insertable; and,  
16 a cutting surface guard fabricated as a portion of said hand piece and  
17 shaped to be in encircling relation about a selected portion of said  
18 cutting surface thereby exposing only a portion of said cutting  
19 surface under the condition of said shaft support means, having said  
20 shaft inserted therein, is mounted within said shaft support channel  
21 of said hand piece and said shaft engaged within said holding means  
22 thereby allowing a user of the arrangement to guide said hand piece  
23 containing the partially guarded tool into the mouth of the horse to  
24 separate said soft tissue from a preselected portion of a tooth with  
25 said cutting surface guard and position the unguarded portion of  
26 said cutting surface against a tooth to remove a selection portion of  
27 said tooth by means of said tool in rotary motion.

28  
29 2 (Previously presented). An arrangement of a tool insertable into the  
30 mouth of a house for the care and maintenance of teeth while

OK to enter upon removal of 20

1 providing protection of soft tissue within the mouth of the horse and  
2 comprising in combination:  
3 an electric rotary motor having a means to hold said tool along the axis  
4 of rotation of said motor, said tool having a tooth cutting surface of a  
5 preselected size and shape;  
6 a shaft having one end mounted to said cutting surface and the other  
7 end attachable to said motor holding means thereby supplying  
8 rotational motion to said tool;  
9 a shaft support means through which said shaft may be removably  
10 inserted, said shaft support means further comprises a bearing  
11 mounted at a preselected position within said shaft support means  
12 and a bearing seal mounted at a position between said bearing and  
13 said cutting surface through which said shaft may be inserted and  
14 supported for rotary motion without binding;  
15 a hand piece having a channel through which said shaft support means  
16 is removably insertable; and,  
17 a cutting surface guard fabricated as a portion of said hand piece and  
18 shaped to be in encircling relation about a selected portion of said  
19 cutting surface thereby exposing only a portion of said cutting  
20 surface under the condition of said shaft support means, having said  
21 shaft inserted therein, is mounted within said shaft support channel  
22 of said hand piece and said shaft engaged within said holding means  
23 thereby allowing a user of the arrangement to guide said hand piece  
24 containing the partially guarded tool into the mouth of the horse to  
25 separate said soft tissue from a preselected portion of a tooth with  
26 said cutting surface guard and position the unguarded portion of  
27 said cutting surface against a tooth to remove a selection portion of  
28 said tooth by means of said tool in rotary motion.

29  
30 <sup>2</sup>3. (Previously presented) The arrangement defined in claim 2<sup>1</sup>  
31 (Previously presented) further comprising a brass sleeve mountable

1 around said shaft under the condition of said shaft being inserted  
2 through said bearing and bearing seal into said shaft support  
3 means, said brass sleeve providing separation between said shaft  
4 and said shaft support means.  
5

6 4. (Cancelled) The arrangement defined in claim 1 further comprising  
7 a flexible shaft having one end adaptively mountable to said motor  
8 thereby supplying rotational motion to said flexible shaft and the  
9 other end having a means to hold said tool along the axis of  
10 rotation of the flexible shaft thereby separating said motor from  
11 said tool so that said motor may be supported at a position remote  
12 from said tool.  
13

14 5. (Cancelled) The arrangement defined in claim 1 further  
15 comprising preselected sized and shaped extended guards  
16 mountable to said cutting surface guard to provide additional  
17 separation between said cutting surface and said soft tissue within  
18 the mouth of the horse.  
19

20 6. (Cancelled) The arrangement defined in claim 1 wherein said hand  
21 piece further comprises an orifice formed near said cutting surface  
22 and a second channel one end in communication with said orifice,  
23 the other end adapted to be removably attachable to a vacuum  
24 source whereby the dust and debris created by the removal of a  
25 selected portion of a tooth may first enter said orifice and then said  
26 second channel to be sucked out of the mouth of the horse and  
27 deposited into said vacuum source.  
28

29 3. (Previously presented) The arrangement in claim 2 (Previously  
30 presented) wherein said shaft support means further comprises  
31 gearing means mounted within said shaft support means and in

1 communication with said shaft to change the rotational motion of  
2 said shaft attached to said motor holding means into reciprocating  
3 motion which may be applied to said cutting surface mounted on  
4 said shaft remote from said gearing means.

5 ~~4~~  
6 ~~8~~. (Previously presented) The arrangement in claim ~~2~~<sup>1</sup> (Previously  
7 presented) wherein said shaft support means further comprises  
8 gearing means mounted within said shaft support means and in  
9 communication with said shaft to change the profile of the shaft by  
10 a preselected angle thereby increasing the range of placement of  
11 said cutting surface of said tool.

12  
13 9. (Cancelled) The arrangement in claim 4 wherein said adaptive  
14 mounting of said flexible shaft is to a motor owned by the user.

15  
16 10. (Cancelled) The arrangement in claim 4 wherein said means to  
17 hold said tool is a handle owned by the user, said flexible shaft  
18 having means to adaptively mount said handle on the end of said  
19 flexible shaft under the condition of said shaft mounted within said  
20 handle.

21  
22 11. (Cancelled) The arrangement in claim 4 further comprising a  
23 clutch mounted with one end in communication with said motor  
24 and another end remote from said motor in communicated with  
25 said flexible shaft thereby providing interruptible transmission of  
26 motion from said motor to said cutting surface in communication  
27 with said flexible shaft.

28 ~~5~~  
29 ~~12~~. (Previously presented) An arrangement of a tool insertable into the  
30 mouth of a horse for the care and maintenance of teeth while

1 providing protection of soft tissue within the mouth of the horse  
2 and comprising in combination:  
3 an electric rotary motor having a means to hold said tool along the axis  
4 of rotation of said motor, said tool having a tooth cutting surface of a  
5 preselected size and shape;  
6 a shaft having one end mounted to said cutting surface and the other  
7 end attachable to said motor holding means thereby supplying  
8 rotational motion to said tool;  
9 a shaft support means through which said shaft may be removably  
10 inserted, said shaft support means further comprises a bearing  
11 mounted at a preselected position within said shaft support means  
12 and a bearing seal mounted at a position between said bearing and  
13 said cutting surface through which said shaft may be inserted and  
14 supported for rotary motion without binding;  
15 a hand piece having a channel through which said shaft support means  
16 is removably insertable; and,  
17 a cutting surface guard fabricated as a portion of said hand piece and  
18 shaped to be in encircling relation about a selected portion of said  
19 cutting surface thereby exposing only a portion of said cutting  
20 surface under the condition of said shaft support means, having said  
21 shaft inserted therein, is mounted within said shaft support channel  
22 of said hand piece and said shaft engaged within said holding means  
23 thereby allowing a user of the arrangement to guide said hand piece  
24 containing the partially guarded tool into the mouth of the horse to  
25 separate said soft tissue from a preselected portion of a tooth with  
26 said cutting surface guard and position the unguarded portion of  
27 said cutting surface against a tooth to remove a selection portion of  
28 said tooth by means of said tool in rotary motion;  
29 a flexible shaft having one end adaptively mountable to said motor  
30 thereby supplying rotational motion to said flexible shaft and the  
31 other end having a means to hold said tool along the axis of rotation



1 of the flexible shaft thereby separating said motor from said tool so  
2 that said motor may be supported at a position remote from said  
3 tool; and,  
4 a clutch mounted with one end in communication with said motor and  
5 another end remote from said motor in communicated with said  
6 flexible shaft thereby providing interruptible transmission of motion  
7 from said motor to said cutting surface in communication with said  
8 flexible shaft, wherein said clutch further comprises means to adjust  
9 the threshold of torque at which said motion is interrupted.

10 <sup>6</sup>  
11 ~~13~~ (Previously presented) The arrangement in claim <sup>5</sup>~~12~~ (Previously  
12 presented) further comprising a clutch housing mountable to said  
13 motor thereby enclosing said clutch and having a mounting to  
14 retain one end of said flexible shaft in communication with said  
15 clutch, said clutch housing having an means for access by the user  
16 to the means to adjust the torque.

17  
18 14. (Cancelled) The arrangement in claim 1 wherein said hand piece  
19 and guard are fabricated from aluminum.

20  
21 15.(Cancelled) The arrangement in claim 14 wherein the exposed  
22 surfaces of said aluminum are anodized.

23 <sup>7</sup>  
24 ~~16~~. An electric motor powered arrangement insertable into the mouth of  
25 a horse for the care and maintenance of equine teeth while providing  
26 protection of soft tissue within the mouth of the horse and  
27 comprising in combination:  
28 a tool having a tooth material removal surface;  
29 a shaft having a first end mounted to said tool and a second end  
30 attachable to said electric motor whereby said tooth material  
31 removal surface has a powered motion;

1 a hand piece fabricated with an internal shaft channel;  
2 a bearing support sleeve;  
3 at least one bearing mounted within said support sleeve at a  
4 preselected position whereby said bearing accepts the insertion of  
5 said shaft through said bearing thereby exposing the end of said  
6 shaft remote from said tooth removal surface, said bearing support  
7 sleeve mounted with said internal shaft channel whereby said  
8 exposed end of said shaft is attachable to said electric motor, said  
9 bearing providing support for said shaft under the condition of said  
10 tooth material removal surface tool being guided into contact with a  
11 preselected tooth and pressed against the tooth until a preselected  
12 portion of the tooth is removed while said tooth material removal  
13 surface is under powered motion;  
14 a protective shield fabricated as part of said hand piece at a preselected  
15 position and shaped to expose a preselected portion of said tooth  
16 material removal surface of said tool retained within said hand piece,  
17 said exposed portion guided into contact with a preselected portion  
18 of the tooth whereby the remaining non-exposed surface is separated  
19 from other portions of the horses mouth including said soft tissue;  
20 and,  
21 a sleeve mountable over said shaft within said shaft hand piece  
22 whereby said sleeve provides additional bearing means between said  
23 shaft and said hand piece without binding.

24 6 7  
25 17. The arrangement defined in claim 16 wherein said bearing  
26 support sleeve means further comprises a bearing mounted at a  
27 preselected position within said bearing support sleeve and a  
28 bearing seal mounted at a position between said bearing and said  
29 cutting surface through which said shaft may be inserted and  
30 supported for rotary motion without binding.  
31

7

1 18. The arrangement defined in claim 16 further comprising a flexible  
2 shaft having one end adaptively mountable to said motor thereby  
3 supplying rotational motion to said flexible shaft and the other end  
4 having a means to hold said tool along the axis of rotation of the  
5 flexible shaft thereby separating said motor from said tool so that  
6 said motor may be supported at a position remote from said tool.

7

7 15  
8 19. The arrangement defined in claim 16 further comprising  
9 preselected sized and shaped extended guards mountable to said  
10 cutting surface guard to provide additional separation between  
11 said cutting surface and said soft tissue within the mouth of the  
12 horse.

15

13 16  
14 20. The arrangement defined in claim 19 wherein said extended guard  
15 further comprises an orifice formed near said cutting surface and a  
16 vacuum channel one end of which is in communication with said  
17 orifice, the other end of said vacuum channel adapted to be  
18 removably attachable to a vacuum source whereby the dust and  
19 debris created by the removal of a selected portion of a tooth may  
20 first enter said orifice and then said channel to be sucked out of  
21 the mouth of the horse and deposited into said vacuum source.

7

22 17  
23 21. The arrangement in claim 16 wherein said bearing support sleeve  
24 further comprises gearing means mounted within said bearing  
25 support sleeve and in communication with said shaft to change the  
26 rotational motion of said shaft attached to said motor holding  
27 means into reciprocating motion which may be applied to said  
28 cutting surface mounted on said shaft remote from said gearing  
29 means.

30

7

1 ~~22~~<sup>18</sup>.The arrangement in claim ~~16~~ wherein said bearing support sleeve  
2 further comprises gearing means mounted within said bearing  
3 support sleeve and in communication with said shaft to change the  
4 profile of the shaft by a preselected angle thereby increasing the  
5 range of placement of said cutting surface of said tool.

9

6 ~~23~~<sup>10</sup>.The arrangement in claim ~~18~~ wherein said adaptive mounting of  
7 said flexible shaft is to a motor owned by the user.  
8

9

9 ~~24~~<sup>11</sup>.The arrangement in claim ~~18~~ wherein said means to hold said tool  
10 is a handle owned by the user, said flexible shaft having means to  
11 adaptively mount said handle on the end of said flexible shaft  
12 under the condition of said shaft mounted within said handle.  
13

9

14 ~~25~~<sup>12</sup>.The arrangement in claim ~~18~~ further comprising a clutch mounted  
15 with one end in communication with said motor and another end  
16 remote from said motor in communicated with said flexible shaft  
17 thereby providing interruptible transmission of motion from said  
18 motor to said cutting surface in communication with said flexible  
19 shaft.  
20

12

21 ~~26~~<sup>13</sup>.The arrangement in claim ~~25~~ wherein said clutch further  
22 comprises means to adjust the threshold of torque at which said  
23 motion is interrupted.  
24

13

25 ~~27~~<sup>14</sup>.The arrangement in claim ~~26~~ further comprising a clutch housing  
26 mountable to said motor thereby enclosing said clutch and having  
27 a mounting to retain one end of said flexible shaft in  
28 communication with said clutch, said clutch housing having an  
29 means for access by the user to the means to adjust the torque.  
30  
31

29. The arrangement in claim <sup>19</sup>~~28~~ wherein the exposed surfaces of said  
aluminum are anodized.